### (19) World Intellectual Property Organization International Bureau



## 

#### (43) International Publication Date 6 May 2004 (06.05.2004)

PCT

# (10) International Publication Number WO 2004/038443 A1

(51) International Patent Classification7:

G01R 33/36

(21) International Application Number:

PCT/IB2003/004589

(22) International Filing Date: 15 October 2003 (15.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

102 49 239.5

23 October 2002 (23.10.2002) DI

(71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Steindamm 94, 20099 Hamburg (DE).

(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CY, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, FR, GB, GD, GE, GH, GM, GR, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SCHULZ, Volkmar

[DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE). GLEICH, Bernhard [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).

(74) Agent: VOLMER, Georg; Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONNECTION LEAD FOR AN ELECTRICAL ACCESSORY DEVICE OF AN MRI SYSTEM



(57) Abstract: A magnetic resonance imaging apparatus is provided with one or more electrical accessory devices, for example, catheters (10) or RF body coils (6), which are intended for use during the examination of an object, as well as with a connection lead (13) which is arranged so as to extend through an examination zone (1) of the magnetic resonance imaging apparatus, which zone can be exposed to an RF field, and to connect the accessory device to a connection unit (12). In order to avoid heating of the connection lead (13) due to currents induced in the connection lead by the RF field, which currents could lead to injury of a patient or damage of the accessory device or the connection unit (12),

the connection lead (13) comprises at least one lead segment (131, 132, ...) which has a length which is limited by at least one inductive coupling element, e.g. a transformer (141, 142, ...; 161, 162, ...) and is unequal to n\*/2, where denotes the RF wavelength and n = 1, 2, 3, ...

) 2004/038443 A1